

Multifunction process calibrators // for electrical signals



Your advantages

Type	MC 75.2
	<ul style="list-style-type: none"> • Highest accuracy & Data logger • Generation of RTD-, TC-, mA- and V signals as well as frequency and pulses • Connection of pressure modules possible

Technical data

Type	MC 75.2
resistance thermometers (RTD)	
Generation and measurement of RTD signals	Pt50, Pt100, Pt200, Pt500, Pt1000, Cu10, Cu50, Ni100, Ni120, Ni1000
Ω -generator function	0...4000 Ω
Ω -measurement function	0...4000 Ω
Accuracy (of reading + const.)	± 0.012 %
Selectable temperature unit	$^{\circ}\text{C} / ^{\circ}\text{F}$
Measurement of multi-wire connections	2 / 3 / 4
Thermocouples (TC)	
Generation and measurement of TC signals	J, K, T, R, S, B, N, E, U, L
mV-generator function	0...100 mV
mV-measurement function	0...100 mV
Accuracy (of reading + const.)	± 0.013 %
Selectable temperature unit	$^{\circ}\text{C} / ^{\circ}\text{F}$
Internal comparison point	± 0.3 $^{\circ}\text{C}$
Current (mA)	
Loop current signal generation	0(4)...24 mA
Loop current signal measurement	0(4)...50 mA
Accuracy (of reading + const.)	± 0.0175 %
Current loop supply	24 V ± 10 %, 22 mA
HART Communication protective resistor	250 Ω
Voltage (V)	
Voltage signal generation	0...20 V
Voltage signal measurement	0...50 V
Accuracy (of reading + const.)	± 0.015 %

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Казахстан (772)734-952-31

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

<https://sika.nt-rt.ru/> || skx@nt-rt.ru

Type	MC 75.2
Continuity (O/C)	
Continuity measurement	0 / C
Switching threshold „open“	1 k Ω
Frequency and pulse (Hz)	
Frequency and pulse signal generation	0.01 Hz...10 kHz
Frequency and pulse signal measurement	0.01 Hz...20 kHz
Accuracy (of reading + const.)	± 0.005 %
Pressure signals (bar)	
Pressure measurement with external pressure module	✓
Editable pressure units	✓
Connection via DIN socket	5-pin

Functions	
Type	MC 75.2
Generation	
High-speed call values	10 points (flexible)
Linear steps and ramps	✓
User-defined synthesiser values	100
User-defined signal output characteristic	10 points
Editable units	✓
Transmitter function simulation	✓
Measurement	
Data memory	10 000 values
Value tables and graphics function	✓
Offset programming for sensor characteristic	✓
Calibration data files and linearisation points	5 x 4 values
User-defined measuring input characteristic	10 points
Editable units	✓
Measured value min. / max.	✓
Averaging function	✓

General data	
Type	MC 75.2
Features	
Sensor connection	8 safety sockets (2 channels) incl. push lock, 4 sets with safety instrument leads (4 mm) and alligator clips (optional)
Power supply	Rechargeable battery including power adapter, 230 VAC / 12 VDC
PC Interface	mini-USB Type B
Operator guidance	Menu with pull-down windows Separate channels for parallel signal processing Programming and control via PC
Display	Multifunction display, double-LCD, 2 x 6 digit, illuminated
Housing	
Version	ABS plastic with protective cover
Dimensions	110 x 210 x 50 mm (H x W x D)
Weight	Approx. 900 g

Multifunction process calibrators // for electrical signals

Order code		
Type	Version	Order number
MC 75.2	Accuracy ± 0.0175 % of reading + const.	EME8AOMC075020

Order code	
Accessories	Order number
DAkkS certificate	EKSIMMON00000D
SIKA works calibration certificate	EKSIMMON00000W
Transport case	EME8GKK3100000
Plug connector 4 mm, red	EME8AOSKLS40RT
Plug connector 4 mm, black	EME8AOSKLS40SW
Software Datacal for MC 75.2	EME8AOMCSDCKA
External pressure module	EME8A0AN601100

External pressure module // for multifunction process calibrator MC 75.2



Ext. pressure module EPM

Technical data	
Type	EPM
Pressure range	-1...1000 bar
Measuring rate	400 measurements / sec.
Digital signals	RS 485
Electrical connection	5-pin 1 m shielded connecting cable
Medium temperature	10...40 °C
Pressure connection	G $\frac{1}{4}$ stainless steel 1.4404
Degree of protection	IP65
Dimensions	Approx. D = 30 mm, L = 110 mm
Weight	Approx. 140 g

Versions				
Type EPM	Model A	Model B	Model C	
Prazision	±0.05 % full scale	±0.025 % full scale	±0.01 % full scale	Max. pressure range
1	-1...1 bar rel. (PR)			2 bar
	0...1 bar abs. (PAA)			
3	-1...3 bar rel. (PR)			5 bar
	0...3 bar abs. (PAA)			
4	-1...4 bar rel. (PA)	-1...4 bar rel. (PA)		20 bar
	0...4 bar abs. (PAA)	0...4 bar abs. (PAA)		
7	-1...7 bar rel. (PA)	-1...7 bar rel. (PA)		
	0...7 bar abs. (PAA)	0...7 bar abs. (PAA)		
10	-1...10 bar rel. (PR)	-1...10 bar rel. (PA)	-1...10 bar rel. (PA)	
	0...10 bar abs. (PAA)	0...10 bar abs. (PAA)	0...10 bar abs. (PAA)	
12	-1...12 bar rel. (PA)	-1...12 bar rel. (PA)		60 bar
	0...12 bar abs. (PAA)	0...12 bar abs. (PAA)		
20	-1...20 bar rel. (PA)	-1...20 bar rel. (PA)		
	0...20 bar abs. (PAA)	0...20 bar abs. (PAA)		
30	-1...30 bar rel. (PR)	-1...30 bar rel. (PA)	-1...30 bar rel. (PA)	
	0...30 bar abs. (PAA)	0...30 bar abs. (PAA)	0...30 bar abs. (PAA)	
40	-1...40 bar rel. (PA)	-1...40 bar rel. (PA)		200 bar
	0...40 bar abs. (PAA)	0...40 bar abs. (PAA)		
70	0...70 bar rel. (PA)	0...70 bar rel. (PA)		
	0...70 bar abs. (PAA)	0...70 bar abs. (PAA)		
100	0...100 bar rel. (PA)	0...100 bar rel. (PA)	0...100 bar rel. (PA)	
	0...100 bar abs. (PAA)	0...100 bar abs. (PAA)	0...100 bar abs. (PAA)	
120	0...120 bar rel. (PA)	0...120 bar rel. (PA)		400 bar
	0...120 bar abs. (PAA)	0...120 bar abs. (PAA)		
135	0...135 bar rel. (PA)	0...135 bar rel. (PA)		
	0...135 bar abs. (PAA)	0...135 bar abs. (PAA)		
160	0...160 bar rel. (PA)	0...160 bar rel. (PA)		
	0...160 bar abs. (PAA)	0...160 bar abs. (PAA)		
200	0...200 bar rel. (PA)	0...200 bar rel. (PA)		
	0...200 bar abs. (PAA)	0...200 bar abs. (PAA)		
300	0...300 bar rel. (PA)	0...300 bar rel. (PA)	0...300 bar rel. (PA)	
	0...300 bar abs. (PAA)	0...300 bar abs. (PAA)	0...300 bar abs. (PAA)	
400	0...400 bar rel. (PA)	0...400 bar rel. (PA)		1000 bar
	0...400 bar abs. (PAA)	0...400 bar abs. (PAA)		
700	0...700 bar rel. (PA)	0...700 bar rel. (PA)	0...700 bar rel. (PA)	
	0...700 bar abs. (PAA)	0...700 bar abs. (PAA)	0...700 bar abs. (PAA)	
1000	0...1000 bar rel. (PA)	0...1000 bar rel. (PA)	0...1000 bar rel. (PA)	
	0...1000 bar abs. (PAA)	0...1000 bar abs. (PAA)	0...1000 bar abs. (PAA)	

PR: Relative pressure measuring cell, ambient pressure as zero point

PAA: Absolute pressure measuring cell, vacuum as zero point

PA: Absolute pressure measuring cell, ambient pressure as zero point

■ Standard pressure ranges

Order code					
Ext. pressure module EPM		EME8A0ACL			
Precision					
0.05% FS			A		
0.025%FS			B		
0.01%FS			C		
Type of pressure					
relativ (PR)			R		
relativ (PA)			R		
absolut (PAA)			A		
Pressure range					
-1(0)...1 bar				0001	
-1(0)...3 bar				0003	
-1(0)...4 bar				0004	
-1(0)...7 bar				0007	
-1(0)...10 bar				0010	
-1(0)...12 bar				0012	
-1(0)...20 bar				0020	
-1(0)...30 bar				0030	
-1(0)...40 bar				0040	
-1(0)...60 bar				0060	
0...70 bar				0070	
0...100 bar				0100	
0...120 bar				0120	
0...135 bar				0135	
0...160 bar				0160	
0...200 bar				0200	
0...300 bar				0300	
0...400 bar				0400	
0...700 bar				0700	
0...1000 bar				1000	
Example order number		EME8A0ACL	A	R	0001

PR: Relative pressure measuring cell, ambient pressure as zero point
PAA: Absolute pressure measuring cell, vacuum as zero point
PA: Absolute pressure measuring cell, ambient pressure as zero point

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-31

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://sika.nt-rt.ru/> || skx@nt-rt.ru